

**Product Information Sheet:**

Date: 20/7/2011

Ref: AP/UTC/01

## AGCO Parts Ultra Trans CV

### AGCO Parts references:

---

VACC3584 20ltr  
VACC3585 205ltr  
VACC3586 1000ltr

### Applications

---

AGCO Parts Ultra Trans CV is a high performance transmission oil, designed for use in demanding CVT transmissions. The product's performance profile enables it to be used in a wide variety of tractor transmission systems, including those with electro-hydraulic controls and oil immersed brake systems. AGCO Parts Ultra Trans CV is extremely shear stability, ensuring effective drive under all loads and operating conditions. The product will protect against wear, foaming and oxidation enabling maximum oil performance.

### Main Benefits

---

- Excellent fluidity at low temperatures.
- Provides optimum friction control in oil immersed brakes and clutch systems.
- Ensures effective hydrostatic drive and response.
- Protects transmission system components under conditions of shock load.

### Specifications

---

Ford ESN-M2C134-D  
New Holland NH - 410B  
Massey Ferguson M1135/1143  
John Deere J20A/C  
API GL4

### Storage

---

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health, Safety and Environment

---

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

## Typical Characteristics

---

Density @ 15 °C (kg/dm <sup>3</sup> )	0,877
Flash point (°C)	204
Viscosity @ 40 °C (cSt)	60,1
Viscosity @ 100 °C (cSt)	9,4
Viscosity index (VI)	140
Pour point (°C)	-42

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised