

---

## Fendt Extra Trans 10W-40 Transmission STOU

### Fendt references:

---

FX991 500 140 5ltr  
FX991 500 131 20ltr  
FX991 500 111 205ltr  
FX991 500 100 Bulk  
FX991 500 101 1000 bulk

Note – Not all sizes are available in all markets. Check local programmes for availability details.

### Applications

---

Fendt Extra Trans 10W-40 has been designed to meet Fendt requirements for the latest transmission technology.

### Main Benefits

---

The excellent characteristics of Fendt Extra Trans 10W-40 are obtained by employing non-conventional base oils. Benefits include:

- Low temperature flow to facilitate starting, and giving rapid response in hydraulic systems.
- Enhanced filterability, and increased power for tools.
- Low volatility, to minimize oil consumption.
- Excellent viscosity stability enables high performance and protection throughout the year and in all climates.

### Specifications

---

MF M-1145  
MF M-1144 / M-1139  
Ford M2C-159B / M2C-121B  
John Deere JDM J27  
ZF TE-ML 06B (includes C,Q,R)  
ZF TE-ML 06D, 06F, 07B  
API GL-4  
Allison C4  
Caterpillar T0-2  
API CG-4/SF  
API CI-4 (Soot control\*)  
MB 227.1  
MB 228.3 (Wear protection\* / Piston Cleanliness\*)  
MIL-L-2104D

\*Supporting data available

## Storage

---

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Health, Safety and Environment

---

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

You should ensure that the product is only used for the purpose specified.

## Typical Characteristics

---

SAE Grade	10W-40
Density at 15 °C	0.866
Viscosity cSt @ 100 °C	12.54
Viscosity cSt @ 40 °C	80.74
Viscosity Index	154
Flash Point (closed) °C	162
Pour Point °C	-37
TBN	11.50

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Product Information Sheet contains details considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

You should always refer to the relevant machine Operators Instruction Manual and only use correct specifications advised.